

Standard Thread Sizes

Change Gear 1	Change Gear 2	Change Gear 3	Change Gear 4	M-Range	Gear Letter	Gear Number	TPI
48	127	127	24	II	A	2	4
48	127	127	24	II	A	3	4.5
48	127	127	24	II	A	4	5
48	127	127	22	II	C	3	5.5
48	127	127	24	II	A	1	6
48	127	127	26	II	C	3	6.5
48	127	127	24	II	A	5	7
48	127	127	24	II	B	4	7.5
48	127	127	24	II	C	1	8
48	127	127	24	I	A	3	9
48	127	127	38	II	C	3	9.5
48	127	127	24	I	A	4	10
48	127	127	24	II	B	5	10.5
48	127	127	22	I	C	3	11
48	127	127	24	I	B	2	12
48	127	127	26	I	C	3	13
48	127	127	24	I	A	5	14
48	127	127	24	I	B	4	15
48	127	127	24	I	C	1	16
48	127	127	24	I	B	1	18
48	127	127	38	I	C	3	19
24	127	127	48	II	A	4	20
48	127	127	24	I	B	5	21
24	127	127	44	II	A	1	22
24	127	127	48	II	B	2	24
24	127	127	52	II	C	3	26
24	127	127	48	II	B	3	27
24	127	127	48	II	A	5	28
24	127	127	48	II	B	4	30
24	127	127	48	I	A	2	32
24	127	127	48	I	A	3	36
24	127	127	38	I	E	5	38
24	127	127	52	I	A	3	39
24	127	127	48	I	A	4	40
24	127	127	44	I	C	3	44
22	127	127	44	I	B	2	48
24	127	127	52	I	C	3	52
24	127	127	48	I	B	3	54
24	127	127	44	I	B	4	55
22	127	127	44	I	A	5	56
24	127	127	48	I	B	4	60
24	127	127	48	I	B	1	72
Change Gear 1	Change Gear 2	Change Gear 3	Change Gear 4	M-Range	Gear Letter	Gear Number	Pitch (mm)
24	127	120	48	I	B	4	0.4
24	127	120	48	I	C	4	0.45

24	127	120	48	I	B	2	0.5
24	127	120	48	I	A	4	0.6
24	127	120	48	I	E	4	0.7
24	127	120	48	I	A	2	0.75
24	127	120	48	II	B	4	0.8
24	127	120	48	II	C	4	0.9
24	127	120	48	II	B	2	1
24	127	120	48	II	A	4	1.2
24	127	120	48	II	D	2	1.25
24	127	120	48	II	E	4	1.4
24	127	120	48	II	A	2	1.5
24	127	120	48	II	E	2	1.75
48	127	120	24	I	C	4	1.8
48	127	120	24	I	B	2	2
48	127	120	24	I	C	2	2.25
48	127	120	24	I	A	4	2.4
48	127	120	24	I	D	2	2.5
48	127	120	24	I	E	4	2.8
48	127	120	24	I	A	2	3
48	127	120	24	II	B	4	3.2
48	127	120	24	I	E	2	3.5
48	127	120	24	II	C	4	3.6
48	127	120	24	II	C	3	4
48	127	120	24	II	C	2	4.5
48	127	120	24	II	A	4	4.8
48	127	120	24	II	D	2	5
48	127	120	24	II	E	4	5.6
48	127	120	24	II	A	2	6
52	127	120	24	II	A	2	6.5
48	127	120	24	II	E	2	7