



NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	B	C	AG	BS	2F	MOUNTING	NO.	REVISION	BY & DATE	CHK	ANG	±7'30"	FINISH	PREV
4	REVISED TABLE - MOUNTING " F1 OR F2 "									RJW 07-25-2007	ML	.X	±.1		
3	ADDED -675 W/182T FR. AND MTG. CN27400-320									CAE 12-07-1999		.XX	±.03		
2	REV. ø.41/.46 WAS 4 HOLES CN26000-635									MRB 06-26-1989		.XXX	±.005		
1	NEW DRAWING CN24224									BLR 05-05-1997		.XXXX	±.0005		
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT										RFP 05-05-1997					
										DIST LB					

TOLERANCES
UNLESS SPECIFIED
DEC. INCHES

DRAWN BLR 05-01-1997

CHK ML 05-05-1997

APPD GK 05-05-1997

SCALE .3125=1

REF

FMF

PREV

TITLE OUTLINE
180T FR. - BB - TS - C'FACE
MATL REF. B-SS68429-REV.2

CAD FILE ss68429

SIZE B DRAWING NO. SS68429 PAGE OF 4 REV.